

Produktinformation


Temperature Sensor 8101/A



Characteristics

- Thermocouple Fe-CuNi (type J); NiCr-Ni (type K)
- RTD Pt100/Pt1000 class B,
- Protective tube, stainless steel 1.4571
- Connection head form BK/PK, DIN 43729, IP65
- Head transmitter optional

Dimensions



Ordering code

1. 2. 3. 4. 5. 6. 7. 8. 9. 10.
 - - - - - - - - -

1. Measuring element	
8101/A	Pt100 class B
2. Number of elements	
1	1 measuring element
2	2 measuring elements
3. Connection type	
2L	2-wire (as 3- and 4-wire applicable)
4. Measuring tip diameter	
9/6	Ø 9mm, sensor tip 40mm reduced to Ø 6mm
5. Fitting length (mm)	
40	40 mm
100	100 mm
160	160 mm
250	250 mm
400	400 mm
600	600 mm
xx	custom length; specify the length in the plain text
6. Neck pipe length (mm)	
0	without
50	50 mm
100	100 mm
xx	custom length; specify the length in the plain text
7. Process connection	
G 1/2	fixed gland 1/2"
G 3/4	fixed gland 3/4"
G1	fixed gland 1"
8. Connection head	
PK	form P (miniature head) IP65
BK	form B (standard) IP65
9. Operating temperature	
400 °C	
10. Options	
00	without option
T4	integrated head transmitter 4...20mA (only head BK)

Stock

8101/A-1-9/6-160-0-G1/2A-BK-500 °C
8101/A-1-9/6-250-0-G1/2A-BK-500 °C
8101/A-1-9/6-400-0-G1/2A-BK-500 °C
8101/A-1-9/6-600-0-G1/2A-BK-500 °C
8101/A-2-9/6-160-0-G1/2A-BK-500 °C