GHM GROUP – Greisinger | GHM Messtechnik GmbH Hans-Sachs-Straße 26 | 93128 Regenstauf | GERMANY Phone +49 9402 9383-0 | Fax +49 9402 9383-33 www.greisinger.de | info@greisinger.de

Produkt Information

G 1791 One-Hand Soil/Compost-**Thermometer**



Front



Robust stainless steel insertion probe

- Ergonomic arrangement of the display and probe
- Fast measurement due to optimized measuring tip
- High resolution and accuracy
- Adjustable alarm function
- Calibratable / traceable
- Long battery life

Characterisitcs

The G 1791 is a convenient insertion thermometer for soft soils, compost, agricultural windrows and bulk materials. The sophisticated probe tip offers a best possible compromise between speed and robustness. The connection between the indicator and probe is welded from solid stainless steel for reliability in tough measurement applications.

Precision, speed and reliability packed in a compact and robust housing makes the instrument a reliable partner for professional users, Made in Germany.



Technical Data

Measuring input Range Precision	-70.0 +250.0 °C (-94.0 +482.0 °F) -20 +100 °C: ± 0.1 K ± 1 Digit
else: ± 0.2 % of measured value ± 2 Digit Reaction time t90 Water (0.4 m/s) ca. 4 s Measuring frequency: 2 measurings/s	
Probe: Diameter: Length: Mounting:	Ø 8 mm 920 mm Probe firmly screwed underneath, similar T-handle
Standard functions: Min/Max/Hold Auto power-off function	
Additional functions:	
	Zero and slope correction Min/Max-Alarm: Display indication, blinking, buzzer
Ambient conditions -20 to 50 °C; 0 to 85 % r.h. (non-condensing)	
Display	3 lines with battery status indicator, Backlight, shatterproof screen,
Operation	4 long-life buttons
Power supply Battery life	2*AA batteries (incl.) >2500 h (without backlight, with backlight >1000 h) 4 level battery status indicator Automatic switch-off, adjustable
Housing	Shatterproof ABS
Protection class Dimensions Weight	Screwed battery compartment IP54 108 * 54 * 28 mm (L*W*H) 275 g incl. battery

Scope of supply

- Handheld with sensor
- Test protocol, optional calibration certificate
- 2xAA batteries
- Manual

Standard articles

Instrument G 1791 •

Spare parts

Spare batteries 2x AA GB-AA-2

Art.-No. 479249

Art.-No. 482472



Compost measuring