GHM GROUP – Greisinger | GHM Messtechnik GmbH Hans-Sachs-Straße 26 | 93128 Regenstauf | GERMANY Phone +49 9402 9383-0 | Fax +49 9402 9383-33 www.greisinger.de | info@greisinger.de

Product Information



GMK 100

Wood and construction moisture meter

Art. Nr. 600105





Rear panel

- **Humidity display in percent**
- Acoustic / visual moisture evaluation
- 18 characteristic curves for wood / building materials
- 2 selectable measuring depths
- Non-destructive measurement at the back of the instrument
- **Hold-Function and Backlight**

Technical specifications

Display: 2 displays: Characteristic curve and

measured value, material moisture

in % or water content in %,

backlight

Moisture evaluation

Visually: Moisture evaluation in 6 levels from

WET (=wet) to DRY (=dry)

Acoustically: Beeper

Measuring depths: 10 mm und 25 mm

Characteristic curves: 18 material curves for wood (with

extensive wood species

classification table) and common building materials; additional reference curve (rEF) for highresolution relative measurements.

Working temperature: -5..+50 °C (Material not frozen)

Storage temperature: -25..+70 °C Power supply: 9 V-Battery

max. 2000 h without backlight Battery life: Power lighting: Approx. 2,5 mA (Auto-Off) Housing: made of impact-resistant ABS, membrane keypad, transparent

pane

Measurements: Approx. 106 x 67 x 30 m

 $(H \times W \times D)$

Weight: Approx. 145 g (ready for use)

Features

The GMK 100 is a capacitive material moisture measuring instrument with direct moisture display in percent and is therefore ideally suited for home and craft applications. Depending on the application either the material moisture u (related to the dry mass) or the water content w (related to the total wet mass) can be displayed.

The measurement is carried out via a measuring plate on the back of the instrument. A switch on the side of the instrument can be used to change the measuring depth. With the aid of measurements at different depths, a statement can be made as to whether, for example, the material is already drying or whether it is a matter of surface moisture. The practical Hold-Function in combination with the backlight are helpful for measuring comfortably in difficult places and often makes this possible in the first place

Fields of application:

Moisture measurement and evaluation of wood, concrete, screed, plaster, etc.

Scope of delivery

- Device
- Battery
- Test protocol
- Operating manual

Accessories

PW25 Art.-Nr, 601368 Test cube



1

PRC Technologies Corp., Ltd. ลาดพร้าว 101 กรุงเทพ 10240 โทรศัพท : 02 530 1714, 02 932 1711 มือถือ : 086 360 8600

www.prctech-th.com

อีเมล : contact@prctech.net LINE ID1 : prctec-info, LINE ID2 : @prctec