

Product information

Round plug connector

Round plug connector



- 4-pin / 5-pin
- packaged
- connection M 12x1, A-coded
- plug straight or angled 90°
- shielding applied to coupling

PIN-assignment

4-pin

- 1 → brown
- 2 → white
- 3 → blue
- 4 → black

5-pin

- 1 → brown
- 2 → white
- 3 → blue
- 4 → black
- 5 → grey

Technical data

Led cross section	0,25 mm ²
End of leds	tinned
protection	IP 67
Cable material	PUR

Ordering code

K - 1. 2. 3. 4. 5.

1.	Number of pin
04	4-pin
05	5-pin
2.	Cable material
PU-	PUR
3.	Cable length
02	2 m
05	5 m
10	10 m
...	Further length on request
4.	Shielding
S	Shielding applied to coupling
5.	Plug outlet
G	straight
W	angled 90°


Female cable socket KB Self assembly




- 4-pin / 5-pin
- Self assembly
- connection M12x1
- plug outlet straight or angled 90°
- not shielded

PIN-assignment

4-pin



5-pin



Technical Data

Max. led cross section	max. 0,75 mm ² / AWG 18
connection	Screw clamps
protection	IP 67
temperature	-40°C .. 85°C
Mechanical life time	> 50 plug cycles

Ordering code

KB - 1. 2.

1.	Number of pin
04	4-pin
05	5-pin
2.	Plug outlet
G	straight
W	angled 90°