



*Screw-in Pt100
with pre-fitted cable or socket*

Description

Basics of ACS Universal RTD form standardized, high-grade platinum measuring resistors with a nominal resistance of 100 ohms at 0 ° C, the tolerance classes AA, A, B - IEC 60751st

ACS Pt100 sensors are characterized by high accuracy and reproducibility and are extremely reliable. The sensing elements are embedded in the protective tube with magnesium oxide and hermetically closed. Thus, a good heat transfer and vibration protection is obtained.

Standard measuring temperatures are -70 ° C. .. +300 ° C;

High temperature versions measure up to +500 ° C / +600 ° C. Low

temperature versions, special materials, process connections and OEM versions are also available.

The given measuring temperature refers to a medium temperature at the probe tip.

For cable versions, for example PTS / PTC and PT100 sensors with connection head, possibly with built-in head transmitter, must be made to the respective maximum temperature of the cable, heads, etc. by use of on-

site isolation or Pt100 with neck tube into consideration.

The measured speed of the individual Pt100 sensor is highly dependent on the operating conditions, the medium to be measured and the mechanical dimensions.

The immersion depth should not be less than 50 mm. Shorter probe lengths, please always clarify with the experienced ACS employees.



technical data

Measuring element:	Platinum resistance element Pt100 / Pt1000, others on request
Temperature ranges:	at the tip: -70 ° C. .. +300 ° C +500 ° C / +600 ° C and low temperature version on request
Tolerance:	AA, A, B - IEC 60751
Signal:	- 1x Pt100: 2 -, 3 -, 4-wire circuit
	- 2x Pt100: in 2x 2x 2-wire or 3-wire circuit
	- Pt100 3x: 3x in 2-wire circuit
	- Free wire ends for self-installation of a head transmitter - Head Transmitter, 4 .. 20mA / 0 .. 10V output, standard, Ex, , Profibus, others on request
Connections:	- terminal compartment in aluminum, plastic or stainless steel housing - Fixed connection cable - shielded PTFE, silicone, PVC, Fiberglass with steel mesh, others on request - Lemo System, M12 system

materials

Materials (process side):	- protective tubes made of seamless stainless steel 1.4571 (AISI 316Ti) - Flanges, process connections: 1.4571 (AISI 316 Ti) - Special materials on request
Materials (connection side):	- Housing: aluminum, stainless steel, polypropylene PP, POM polyoxymethylene - Cable Material, see "Connection"

Order code PTK



- sensor type**
- 1 Pt100, 2-wire
 - 2 **1x Pt100, 3-wire** (preferred)
 - 3 1x Pt100, 4-wire
 - 4 2x Pt100, 2-wire (double Pt100 only from ø 5 mm)
 - 5 2x Pt100, 3-wire (double Pt100 only from ø 5 mm)

accuracy class (bei 2-fold Pt100 price x 2)

B class B, up to +200°C (preferred type)

A class A, up to +200°C

C class AA (formerly class 1/3B), up to +200°C

Y Special version for example High temperature,

design

A see dimension drawing A (thread G 1/4"; G 3/8"; G 1/2" or M20)

B see dimension drawing B (thread from M8)

C see dimension drawing C (thread from M6)

D see dimension drawing D (thread from M6)

F see dimension drawing F

thread

A screw-in thread M6

H screw-in thread M10 x 1

D screw-in thread M8

N screw-in thread G 3/8"

F screw-in thread M8 x 1

O screw-in thread G 1/2"

G screw-in thread M10

P screw-in thread G 1/4"

T screw-in thread M20

Y andere Anschlüsse

material, probe diameter, process side

T 1.4571/ 3 mm (design C + D)

U 1.4571/ 5 mm (design B)

V 1.4571/ 10 mm (design A)

Z 1.4571/ 8 mm (design A)

O 1.4571/ probe diameter corresponding thread (design

cable

A PVC

B PTFE (only with 1x Pt100 possible) (preferred type)

C silicone

D fiberglass with steel mesh up to +300°C (only 3-wire)

L plug connector LEMO SA 4-pole size 1 up to +80°C

Y Sonderausführung

cable length

1 1000 mm silicone / PVC

A PTFE / fiberglass

2 2000 mm silicone / PVC

B PTFE / fiberglass

5 5000 mm silicone / PVC

C PTFE /

S special fiberglass

0 length but cable with plug version

strain relief


O relieved (limited water resistance) (preferred type)

2 tight rolled, IP 67, only mit PTFE-cable

S wasterproof IP 68 version

Y special version

length L1 sensor in mm (standard lengths: 50 | 100 | 150 mm)



order
code

**PT
K**

mm

PRC Technologies Corp., Ltd. ลาดพร้าว 101 กรุงเทพฯ 10240

โทรศัพท์ : 02 530 1714, 02 932 1711 มือถือ : 086 360 8600

อีเมล : contact@prctech.net LINE ID1 : prctec-info, LINE ID2 : prcsense